



www.c-innovation.com

SUPERIOR ROV SOLUTIONS FOR ALL MARKETS



Model	HD™	UHD™
Depth Rating	3,000msw [4,000msw Option]	4,000msw
Dimensions	2.5m x 1.7m x 1.9m	3.0m x 1.9m x 2.0m
Through-Frame Lift	3,000kg	3,500kg
Weight in Air	3,500kg	5,000kg
Payload	250kgf	300kgf
HPU Power	150shp	200shp
Thrusters	(7) Sub-Atlantic SA380-40	(7) Sub-Atlantic SA420
Bollard Pull Forward	900kgf	1,200kgf
Bollard Pull Lateral	900kgf	1,200kgf
Bollard Pull Up	850kgf	1,000kgf
Bollard Pull Down	850kgf	1,000kgf
Aux Hydraulics	72lpm at 207 Bar	120lpm at 207 Bar
Spare Functions	4-11	11xNG3 Low Flow Functions
Tooling Valvepack	3F Option	3F Standard
Controls System	(4) Schilling DTS™ Nodes	(5) Schilling DTS™ Nodes
Lighting	26vdc	120vac
TMS Type	Schilling HD™ Top Hat	Schilling XE™ Top Hat
Tether	28mm Neutrally Buoyant	35mm Neutrally Buoyant
Tether Length	425m	850m
TMS Drive Type	Electric Drive	Hydraulic Drive
Manipulator 1	All Schilling Manipulators	All Schilling Manipulators
Manipulator 2	All Schilling Manipulators	All Schilling Manipulators
Umbilical	28.5mm OD	39.5mm OD
LARS SWL	9.5Te	13.5Te